

# Anwendungstabelle **EKAMAT** Bogen aus Grobkorn-Aluminium

## Anwendung für 90°-Bogen (Norm 3)

Rohr Außen- φ	Dämmdicken											
	13	20	25	30	35	40	50	60	70	80	100	
12		12-20										
15	15-13			15-30								
18	18-13	18-20	28-20	18-30	28-30	18-40	42-40					
22	22-13	22-20	35-20	22-30	35-30	22-40	42-40					
28	28-13	28-20	22-30	28-30	22-40	28-40	28-50					
35	22-20	35-20	42-20	35-30	42-30	35-40	35-50					
38		22-30		38-30		38-40						
42/44	28-20	42-20	35-30	42-30	35-40	42-40	42-50	42-60				
48	35-20	48-20	42-30	48-30	60-30	48-40	48-50	48-60				
54				54-30	42-40	54-40	54-50	76-50				
57/60	42-20	60-20	60-25	60-30	70-30	60-40	60-50	60-60		108-60		
64		48-30	54-30	64-30	76-30	64-40	89-40	64-60	89-60	108-60		
70	60-20	48-30	60-30	70-30	60-40	70-40	89-40	76-60	76-70	76-80		
76		60-30	64-30	76-30	89-30	76-40	76-50	76-60	76-70	76-80		
89		89-20	76-30	89-30	102-30	89-40	89-50	89-60	108-60	89-80	89-100	
102		89-30	102-30	102-30	108-30	89-50	108-50	108-60	127-60	108-80		
108		89-30	102-30	108-30	114-30	108-40	108-50	108-60	127-60	108-80	114-100	
114		102-30	108-30	114-30	108-40	114-40	140-40	114-60	133-60	133-70	114-100	
127		108-30	114-30	108-40	114-40	127-40	108-60	127-60	108-80	169-60		
133		114-30	108-40	114-40	127-40	76-70	133-50	133-60	133-70	114-100	133-100	
140		108-40	114-40	127-40		140-40	127-60	140-60	169-60	114-100	140-100	
159		114-40	127-40	140-40		127-60	140-60	133-70	114-100	133-100	159-100	
169			140-40	108-60		127-60	169-50	169-60	114-100	140-100		
219							133-100		159-100			



Standard-Materialstärke: 200μ, FETT gedruckte Größen werden aus der 300μ-Folie hergestellt.

## Anwendung für 90° und 45° SML, KG und HT Bogen

### 90°

DN	Dämmdicke (mm)		
	20	30	40
50	42-30	42-40	89-30
70	60-30	60-40	89-40
100	89-30	76-50	89-50
125	114-30	76-60	76-70
150	127-40	114-60	133-60
200	89-80	133-70	114-100

### 45°

DN	Dämmdicke (mm)		
	20	30	40
50	102	128	154
70	128	154	167
100	154	167	193
125	167	193	
150	193		258
200			

① SML (System Muffenlos) - Abwasserrohre aus Grauguss

① KG = Kanalgrundrohr

① HT = Hochtemperaturrohr