

## Radien-Tabelle

für genormte Rohrbogen 90° (Maße in mm)

Rohr ø		DN	Tempergussfittings DIN 2950 für Wasserrohre		Einschweißbogen DIN 2605/2606 für Heizungsrohre		Handgebogene Rohrbogen für Heizungsrohre*
Zoll	äuß.ø mm		Winkel A1	Bogen G1	Bauart		
					3D	5D	
3/8	17,2	10	15	29	23		
1/2	21,3	15	15	32	26	43	60
3/4	26,9	20	18	42	29	58	95
1	33,7	25	21	52	38	73	105
	38				45	83	
1 1/4	42,4	32	26	70	48	93	135
	44,5				51	98	
1 1/2	48,3	40	31	82	62	108	
	57				72	128	
2	60,3	50	34	100	76	135	
	63,5				83	143	
	70				92	160	
2 1/2	76,1	65	42	130	95	175	
3	88,9	80	48	155	115	205	
	101,6				134	238	
	108	100			143	253	
4	114,3		60	200	153	270	
	127				178	300	
	133	125			181	313	
5	139,7		75		191	330	
	159				216	375	
6	168,3	150	91		229	390	
	177,8				250	430	
	193,7	175			270	455	
8	219,1	200			305	510	
	244,5				340	580	
	267				378	635	
10	273	250			381	650	
12	323,9	300			457	775	
14	355,6	350			534	850	
	406,4	400			610	970	
	419				610	1000	
20	508	500			762	1245	

\* Radius wird vom Biegesegment der verwendeten Rohrbiegemaschine bestimmt.

